

Handled by, department
Mikael Lindgren
Measurement Technology
+46 10 516 57 13, Mikael.Lindgren@sp.se

Teletec Connect AB
Veterinärgränd 6
121 63 Johanneshov

Testing of passive infrared detector Optex SX-360Z according to CLC/TS 50131-2-2

(2 appendices)

SP Technical Research Institute of Sweden has performed functional tests of a passive infrared detector in accordance with the CENELEC standard CLC/TS 50131-2-2:2004.

Identification

Your reference: Sebastian Håkansson/2010-11-12
Delivery of test objects: 2010-11-12
Status of test objects: Without complaint
Manufacturer: Optex
Model: SX-360Z
Grade: 2
Lens: N/A
Settings: Sensitivity = High, Zoom = A, Pulse count = 2
Delivered documentation: Installation Instructions No. 59-0527-5 0904-30

Specification

Detection area: \varnothing 18 m, see diagram in Appendix
Mounting height: 2.4 – 4.8 m.

Date of test

December 13 – 23, 2010.

Summary of test results

The detector fulfils the requirements.

Measurement conditions

The measurements are made in a temperature stabilized laboratory with the temperature $+23\text{ °C} \pm 2\text{ °C}$. The full length of the laboratory is 35 m. The infrared detector is placed on a photogoniometer on 4.8 m height. The goniometer is turned horizontally to select each test point.

Standard walk test target (SWT) temperature difference: $3\text{ °C} \pm 0.3\text{ °C}$

Instrument code: Photogoniometer, IR-thermometer

Measurement accuracy

Angle of detection: $\pm 0.1^\circ$
Distance: $\pm 0.2\text{ m}$
Temperature: $\pm 0.2\text{ °C}$

SP Technical Research Institute of Sweden

Postal address
SP
Box 857
SE-501 15 BORÅS
Sweden

Office location
Västeråsen
Brinellgatan 4
Borås

Phone / Fax / E-mail
+46 10 516 50 00
+46 33 13 55 02
info@sp.se

This document may not be reproduced other than in full, except with the prior written approval of SP.

The reported expanded uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k = 2$, which for a normal distribution corresponds to a coverage probability of approximately 95 %. The standard uncertainty of measurement has been determined in accordance with EA Publication EA-4/02.

Measurement method

The testing is performed in accordance with applicable parts of standard CLC/TS 50131-2-2:2004 and SP method no 4240.

Measurement result

The result of the testing is presented following the paragraphs of the standard.

4.4.1 Immunity to air flow

Increase of air temperature from ambient to 40 °C with gradient 5 °C/min. Stabilization at 40 °C during 4 minutes. Ramp down with heat off and stabilize at ambient for 2 min. The cycle is repeated 5 times.

No alarms were detected. The detector fulfils the requirement.

4.4.2 Immunity to visible and near infrared radiation

A light source is placed at 5 meters distance, scanning over the detector at a speed of 0.5 m/s. A double pane of glass is placed in front of the detector. A total of 10 scans are performed.

No alarms were detected. The detector fulfils the requirement.

6.4.1 Detection within and across the boundary

A Standard Walk Test target was used in each test point, moving at 1.0 m/s (across) and 0.3 m/s (within) a total of 3 m at $\pm 45^\circ$ angle to the detector radial line. The detector set an alarm at 100 % of the test points, see sketch in Appendix.

The detector fulfils the requirement (95 %).

6.4.2 Detection at high velocity and with intermittent movement

A Standard Walk Test target was used, moving at 2.0 m/s along the prescribed lines. Intermittent movement is not required for a Grade 2 detector. The detector set an alarm at all test points.

The detector fulfils the requirement.

6.4.3 Verify the close-in detection performance

A Standard Walk Test target was used, moving at 0.4 m/s along the prescribed lines. The detector set an alarm at all test points.

The detector fulfils the requirement.

6.4.4 Verify the effect of control adjustments on detection

The detector does not offer any control adjustments, the test is not applicable.

6.4.5 Verify the significant reduction of specified range

The test is not required for a Grade 2 detector.

Remark

The result in this test report is valid only for the item tested.

SP Technical Research Institute of Sweden Measurement Technology - Communication

Mikael Lindgren
Technical Manager/Officer

Appendices

Installation Instructions

Results from Walk Test







Appendix 1

Appendix 1





Installation Instructions

- Initial Alarm Memory (SA-3BUZV)
- LED Remote Control Terminal

I. INSTALLATION HINTS

<p>① </p> <p>Avoid direct sunlight.</p>	<p>② </p> <p>Avoid looking directly at air conditioning or heating vents.</p>	<p>③ </p> <p>Avoid vapor or high humidity that can cause condensation.</p>
<p>④ </p> <p>Avoid Curtain, Screen, etc. blocking detection area.</p>	<p>⑤ </p> <p>Do not install outdoors.</p>	<p>⑥ </p> <p>Install within 8~16ft (2.4~5m) height from floor.</p>

II. DETECTION AREA

<p>TOP VIEW</p>  <p style="text-align: center;">φ 60 ft (18m)</p>	<p>SIDE VIEW</p> <p>ZOOM "A" Position (See Section VII.)</p>  <p style="text-align: center;">ZOOM</p> <p>ZOOM "C" Position (See Section VII.)</p>  <p style="text-align: center;">ZOOM</p> <p>ZOOM "E" Position (See Section VII.)</p> 
--	---

Appendix 2

Appendix 2

Result from Walk Test Detection Performance
within and across the boundary
Detector 6

