


Introduction to PyTorch

Deep Learning Frameworks



Caffe
UC Berkeley

theano
Montreal



TensorFlow
Google

mxnet
Amazon

ONNX
Microsoft

DL4J
Eclipse (IBM)



Google

Why PyTorch

- Implements many necessary modules for DL
- Quick prototyping
- Easy debugging
- “Pythonic” programming style

Today

- Tensors ~50%
- nn Module ~20%
- Autograd ~30%

Tensors


```
# creation from data
data = [[1, 2], [3, 4]]
x_data = torch.tensor(data)

tensor([[1, 2],
       [3, 4]])
```

```
# creation from numpy array
np_array = np.array(data)
x_np = torch.from_numpy(np_array)

tensor([[1, 2],
       [3, 4]])
```

(Almost) Just like NumPy!



Tensor Attributes



shape →
dtype →
device →

$$x_data = \begin{pmatrix} 1 & 2 \\ 3 & 4 \end{pmatrix}$$

```
x_data.shape
```

```
torch.Size([2, 2])
```

```
x_data.dtype
```

```
torch.int64
```

```
x_data.device
```

```
device(type='cpu')
```

Managing Device

Do we have GPU resources available?

```
torch.cuda.is_available()
```

True

How many GPU resources are available?

```
torch.cuda.device_count()
```

1

Moving a Tensor from one device to another.

```
print(x_data.device)
x_gpu = x_data.to('cuda')
print(x_gpu.device)
```

cpu
cuda:0



Tensor Operations

```
# initialization
a = torch.tensor([[1, 2, 3], [4, 5, 6], [7, 8, 9]])
b = torch.eye(3)

print(f"a: {a}")
print(f"b: {b}")
```

```
a: tensor([[1., 2., 3.],
           [4., 5., 6.],
           [7., 8., 9.]])
b: tensor([[1., 0., 0.],
           [0., 1., 0.],
           [0., 0., 1.]])
```

Basic Operations

Just like NumPy!

$$a = \begin{pmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 7 & 8 & 9 \end{pmatrix} b = \begin{pmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{pmatrix}$$

a + b

```
tensor([[ 2.,  2.,  3.],
        [ 4.,  6.,  6.],
        [ 7.,  8., 10.]])
```

a / b

```
tensor([[1., inf, inf],
        [inf, 5., inf],
        [inf, inf, 9.]])
```

a - b

```
tensor([[0.,  2.,  3.],
        [4.,  4.,  6.],
        [7.,  8.,  8.]])
```

a ** b

```
tensor([[1.,  1.,  1.],
        [1.,  5.,  1.],
        [1.,  1.,  9.]])
```

a * b

```
tensor([[1.,  0.,  0.],
        [0.,  5.,  0.],
        [0.,  0.,  9.]])
```

a @ b

```
tensor([[1.,  2.,  3.],
        [4.,  5.,  6.],
        [7.,  8.,  9.]])
```

In-place Operations

Just like NumPy!

```
a + b  
a
```

```
tensor([[1., 2., 3.],  
       [4., 5., 6.],  
       [7., 8., 9.]])
```

```
a += b  
a
```

```
tensor([[ 2.,  2.,  3.],  
       [ 4.,  6.,  6.],  
       [ 7.,  8., 10.]])
```

```
a -= b  
a
```

```
tensor([[0., 2., 3.],  
       [4., 4., 6.],  
       [7., 8., 8.]])
```

$$a = \begin{pmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 7 & 8 & 9 \end{pmatrix} b = \begin{pmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{pmatrix}$$

```
a.clamp(2, 5)  
a
```

```
tensor([[1., 2., 3.],  
       [4., 5., 6.],  
       [7., 8., 9.]])
```

```
a.clamp_(2, 5)  
a
```

```
tensor([[2., 2., 3.],  
       [4., 5., 5.],  
       [5., 5., 5.]])
```

Tensor Operations

Indexing and slicing – just like NumPy!

$$a = \begin{pmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 7 & 8 & 9 \end{pmatrix} b = \begin{pmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{pmatrix}$$

Indexing

```
a[0, 0]
```

```
tensor(1.)
```

```
a[1, 2]
```

```
tensor(6.)
```

```
a[0, :] row
```

```
tensor([1., 2., 3.])
```

```
a[0, :].shape
```

```
torch.Size([3])
```

Slicing

```
a[:, 0] column
```

```
tensor([1., 4., 7.])
```

```
a[:, 0].shape
```

```
torch.Size([3])
```

$$a = \begin{pmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 7 & 8 & 9 \end{pmatrix} b = \begin{pmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{pmatrix}$$

Tensor Operations

Concatenation, splitting, stacking, etc. – just like NumPy!

Concatenation

```
torch.cat((a, b))
```

```
tensor([[1., 2., 3.],
       [4., 5., 6.],
       [7., 8., 9.],
       [1., 0., 0.],
       [0., 1., 0.],
       [0., 0., 1.]])
```

```
torch.cat((a, b)).shape
```

```
torch.Size([6, 3])
```

```
torch.cat((a, b), dim=1)
```

```
tensor([[1., 2., 3., 1., 0., 0.],
       [4., 5., 6., 0., 1., 0.],
       [7., 8., 9., 0., 0., 1.]])
```

```
torch.cat((a, b), dim=1).shape
```

```
torch.Size([3, 6])
```

dim → axis
Pytorch → Numpy

Tensor Operations

reshape – just like NumPy!

```
a.shape  
  
torch.Size([3, 3])  
  
a.reshape((1, 9))  
  
tensor([[1., 2., 3., 4., 5., 6., 7., 8., 9.]])  
  
a.reshape((1, 9)).shape  
  
torch.Size([1, 9])
```

$$a = \begin{pmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 7 & 8 & 9 \end{pmatrix} b = \begin{pmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{pmatrix}$$

squeeze & unsqueeze

```
a_unsqueeze = a.unsqueeze(dim=0)
```

```
a_unsqueeze.shape
```

```
torch.Size([1, 3, 3])
```

```
a_unsqueeze.squeeze_()
```


```
tensor([[1., 2., 3.],  
       [4., 5., 6.],  
       [7., 8., 9.]])
```

```
a_unsqueeze.shape
```

```
torch.Size([3, 3])
```

Vectorization & GPU

- GPUs have many small “cores” => many small operations can run in parallel



Case Study: Matrix Multiplication

Case 1: Nested for loops

```
res = torch.zeros((size, size))
for i in range(size):
    for j in range(size):
        row = x[:, i]
        col = y[:, j]
        res[i, j] = torch.sum(row * col)
```

18.8 seconds

Case 2: Single for loop

```
res = torch.zeros((size, size))
for i in range(size):
    row = x[:, i]
    res[i, :] = torch.sum(row * y, dim=0)
```

132 milliseconds

Case 3: Vectorized Operation

```
torch.
```

25.8 milliseconds

Case 4: using a GPU

```
x_g = x.to('cuda')
y_g = y.to('cuda')
torch.mm(x_g, y_g)
```

0.57 milliseconds

DON'T Do It Yourself!

- Use built-in vectorized operations instead of implementing them yourself!
- Use GPU resources when possible.



Your Implementation



Pytorch's
Implementation



Pytorch's Implementation
on GPU

Elementwise Operations

- $+, -, *, /, \min, \max, \dots$

```
c = a + b  
d = a - b  
...
```

Linear Algebra

- `torch.matmul / @`

```
mat = torch.rand(size=(N, M))          # N×M
vec = torch.rand(size=(M, ))           # M
out = mat @ vec                      # N
```

```
mat1 = torch.rand(size=(N, K))          # N×K
mat2 = torch.rand(size=(K, M))           # K×M
out = mat1 @ mat2                     # N×M
```

```
bmat1 = torch.rand(size=(B, N, K))    # B×N×K
bmat2 = torch.rand(size=(B, K, M))    # B×K×M
out = bmat1 @ bmat2                  # B×N×M
```

Pro Tip: Broadcasting

- Fully matching dimensions may be redundant:
 - Add a single row to each row in a matrix.

```
a = torch.rand(size=(N, 1))                      # N×1
b = torch.rand(size=(1, M))                      # 1×M
out = a + b                                      # N×M
```

- Multiply a batch of matrices by a single matrix.

```
bmat1 = torch.rand(size=(B, N, K))    # B×N×K
mat2 = torch.rand(size=(K, M))          # K×M
out = bmat1 @ mat2                    # B×N×M
```

Advanced Tensor Multiplication

- Einstein summation convention (`torch.einsum`):
 - Each dimension in each operand has a letter.
 - Multiply over dimensions with the same letter.
 - Sum over dimensions which letters are not in the output.

```
mat = torch.rand(size=(N, M))                      # N×M
vec = torch.rand(size=(M, ))                         # M

out = torch.einsum( , mat, vec) # N
```

Advanced Tensor Multiplication

- Batch matrix-multiplication with `torch.einsum`:

$$\mathbf{out}[b, n, m] = \sum_k \mathbf{mat1}[b, n, k] \cdot \mathbf{mat2}[b, k, m]$$

```
mat1 = torch.rand(size=(B, N, K))                      # B×N×K
mat2 = torch.rand(size=(B, K, M))                      # B×K×M

out = torch.einsum(, mat1, mat2) # B×N×M
```

Advanced Tensor Multiplication

- More complex example:


$$\mathbf{out}[i, j, k] = \sum_l \sum_m \mathbf{x}[i, k, m, l, j] \cdot \mathbf{y}[i, l, j, k] \cdot \mathbf{z}[i]$$

```
x = torch.rand(size=(I, K, M, L, J))
y = torch.rand(size=(I, L, J, K))
z = torch.rand(size=(I,))

out = torch.einsum("ikmlj,iljk,i->ijk", x, y, z)
```

Gather

- Sample elements from a tensor according to an index.



Gather

- Sample elements from a tensor according to an index.

```
dim = 0
src = torch.rand(size=(4, 4, 6)) # C, H, W
index = torch.randint(low=0, high=4, size=(1, 4, 6))
#index = torch.randint(low=0, high=src.size(dim), size=(num_samples, src.size(1), src.size(2)))

# naive
out = src.zeros_like(size=(1, 4, 6))
for i in range(1):
    for j in range(4):
        for k in range(6):
            out[i, j, k] = src[index[i, j, k], j, k]

# vectorized
out = torch.gather(src, dim, index)
```

Gather


- Sample elements from a tensor according to an index.

```
dim = 1
src = torch.rand(size=(4, 4, 6))
index = torch.randint(low=0, high=4, size=(4, 1, 6))
#index = torch.randint(low=0, high=src.size(dim), size=(src.size(0), num_samples, src.size(2)))

# naive
out = src.zeros_like(size=(4, 1, 6))
for i in range(4):
    for j in range(1):
        for k in range(6):
            out[i, j, k] = src[i, index[i, j, k], k]


# vectorized
out = torch.gather(src, dim, index)
```

Gather and Scatter




0	1	...			
0	3	...			
...			

Gather →




→ **Scatter**



Scatter (Add)

- The opposite (backward) of *Gather*.



Scatter (Add)


- The opposite (backward) of *Gather*.

```
dim = 0
src = torch.rand(size=(1, 4, 6))
index = torch.randint(low=0, high=4, size=(1, 4, 6))
#index = torch.randint(low=0, high=size, size=src.size())

# naive
out = src.zeros_like(size=(4, 4, 6))
for i in range(1):
    for j in range(4):
        for k in range(6):
            out[index[i, j, k], j, k] += src[i, j, k]

# vectorized in-place (assume out.shape == (4, 4, 6))
out.scatter_add_(dim, index, src)
```

Building a Neural Network



Building a Neural Network

`nn.Module`

`__init__()`

`forward()`

Building a Neural Network

```
INPUT_SIZE = 224
C = 10 # num classes

class MLP(nn.Module):

    def __init__(self):
        super(MLP, self).__init__()
        self.flatten = nn.Flatten()
        self.fc1 = nn.Linear(INPUT_SIZE*INPUT_SIZE, 256)
        self.relu1 = nn.ReLU()
        self.fc2 = nn.Linear(256, 512)
        self.relu2 = nn.ReLU()
        self.fc3 = nn.Linear(512, C)

    def forward(self, x):
        x = self.flatten(x)
        x = self.fc1(x)
        x = self.relu1(x)
        x = self.fc2(x)
        x = self.relu2(x)
        x = self.fc3(x)
        return x
```

Initialize

```
B = 10 # batch size

input = torch.randn(B, 1, INPUT_SIZE, INPUT_SIZE)
model = MLP()
```

input shape: $(B, 1, H, W)$

output shape: (B, C)

Run with CPU

```
output = model(input)
```

7.96 milliseconds

Run with GPU

```
gpu_model = model.to('cuda')
gpu_input = input.to('cuda')

gpu_output = gpu_model(gpu_input)
```

0.58 milliseconds

Building a Neural Network

```
INPUT_SIZE = 224
C = 10 # num classes

class MLP(nn.Module):

    def __init__(self):
        super(MLP, self).__init__()
        self.flatten = nn.Flatten()
        self.fc1 = nn.Linear(INPUT_SIZE*INPUT_SIZE, 256)
        self.relu1 = nn.ReLU()
        self.fc2 = nn.Linear(256, 512)
        self.relu2 = nn.ReLU()
        self.fc3 = nn.Linear(512, C)


    def forward(self, x):
        x = self.flatten(x)
        x = self.fc1(x)
        x = self.relu1(x)
        x = self.fc2(x)
        x = self.relu2(x)
        x = self.fc3(x)
        return x
```

Using Sequential

```
seq_model = nn.Sequential(
    nn.Flatten(),
    nn.Linear(INPUT_SIZE*INPUT_SIZE, 256),
    nn.ReLU(),
    nn.Linear(256, 512),
    nn.ReLU(),
    nn.Linear(512, 10),
)

output = seq_model(input)
```


Backpropagation



Reminder Example

- Data: $x, y \in \mathbb{R}$
- Hypothesis: $\hat{y} = x \cdot w$
- Loss: $L = (\hat{y} - y)^2$
- SGD: $w \leftarrow w - \alpha \cdot \boxed{\frac{\partial L}{\partial w}}$


Tensor Attributes - Autograd



`grad` - gradient for this tensor

`grad_fn` – reference for a function, used to obtain this tensor

Tensor Attributes - Autograd



```
x = torch.tensor([2.])
w = torch.tensor([1.],
    requires_grad=True)
y = torch.tensor([3.])
```

```
y_hat = x * w
L = (y_hat - y) ** 2
```

```
L.backward()
```

```
print(w.grad)
print(x.grad)
```


```
tensor([-4.])
None
```

Computational Graph

- Directed graph where the nodes correspond to operations or variables
- Can be used to differentiate via the *chain rule*


Computational Graph

- Data: $x, y \in \mathbb{R}$
- Hypothesis: $\hat{y} = x \cdot w$
- Loss: $L = (\hat{y} - y)^2$
- SGD: $w \leftarrow w - \alpha \cdot \frac{\partial L}{\partial w}$




Computational Graph

- Data: $x, y \in \mathbb{R}$
- Hypothesis: $\hat{y} = x \cdot w$
- Loss: $L = (\hat{y} - y)^2$
- SGD: $w \leftarrow w - \alpha \cdot \frac{\partial L}{\partial w}$




Computational Graph

- Data: $x, y \in \mathbb{R}$
- Hypothesis: $\hat{y} = x \cdot w$
- Loss: $L = (\hat{y} - y)^2$
- SGD: $w \leftarrow w - \alpha \cdot \frac{\partial L}{\partial w}$




Computational Graph

- Data: $x, y \in \mathbb{R}$
- Hypothesis: $\hat{y} = x \cdot w$
- Loss: $L = (\hat{y} - y)^2$
- SGD: $w \leftarrow w - \alpha \cdot \frac{\partial L}{\partial w}$




Computational Graph

- Data: $x, y \in \mathbb{R}$
- Hypothesis: $\hat{y} = x \cdot w$
- Loss: $L = (\hat{y} - y)^2$
- SGD: $w \leftarrow w - \alpha \cdot \frac{\partial L}{\partial w}$



Computational Graph

- Data: $x, y \in \mathbb{R}$
- Hypothesis: $\hat{y} = x \cdot w$
- Loss: $L = (\hat{y} - y)^2$
- SGD: $w \leftarrow w - \alpha \cdot \frac{\partial L}{\partial w}$




Computational Graph

- Data: $x, y \in \mathbb{R}$
- Hypothesis: $\hat{y} = x \cdot w$
- Loss: $L = (\hat{y} - y)^2$
- SGD: $w \leftarrow w - \alpha \cdot \frac{\partial L}{\partial w}$

Chain rule:

$$\frac{\partial L}{\partial w} = \frac{\partial L}{\partial a} \cdot \frac{\partial a}{\partial \hat{y}} \cdot \frac{\partial \hat{y}}{\partial w}$$




Static VS Dynamic Graph

- Static graph: graph's structure is fixed, then inject data
- Dynamic graph: graph's structure is defined on the fly


Static Graph

- First define the graph, then inject data




Dynamic Graph

- Define variables and their relations. The graph is defined implicitly



Static VS Dynamic Graph



Computational Graph in PyTorch

- Dynamic
- Created in the forward pass (on the fly)
 - Unless `torch.no_grad()` was used
- Deleted in the backward pass

CG in PyTorch: forward

```
x = torch.tensor([2.])
w = torch.tensor([1.],
    requires_grad=True)
y = torch.tensor([3.])
```

```
y_hat = x * w
L = (y_hat - y) ** 2
```

```
L.backward()
```

$y=3$
y.grad=None

$x=2$
x.grad=None


$w=1$
w.grad=None

CG in PyTorch: forward

```
x = torch.tensor([2.])
w = torch.tensor([1.],
    requires_grad=True)
y = torch.tensor([3.])

y_hat = x * w
L = (y_hat - y) ** 2


L.backward()
```



CG in PyTorch: forward

```
x = torch.tensor([2.])
w = torch.tensor([1.],
    requires_grad=True)
y = torch.tensor([3.])



y_hat = x * w
L = (y_hat - y) ** 2
L.backward()
```



CG in PyTorch: forward

```
x = torch.tensor([2.])
w = torch.tensor([1.],
    requires_grad=True)
y = torch.tensor([3.])

y_hat = x * w
L = (y_hat - y) ** 2
L.backward()
```





ctx

CG in PyTorch: backward

```
x = torch.tensor([2.])
w = torch.tensor([1.],
    requires_grad=True)
y = torch.tensor([3.])

y_hat = x * w
L = (y_hat - y) ** 2

L.backward()
```




ctx

CG in PyTorch: backward

```
x = torch.tensor([2.])
w = torch.tensor([1.],
    requires_grad=True)
y = torch.tensor([3.])

y_hat = x * w
L = (y_hat - y) ** 2

L.backward()
```




CG in PyTorch: backward

```
x = torch.tensor([2.])
w = torch.tensor([1.],
    requires_grad=True)
y = torch.tensor([3.])

y_hat = x * w
L = (y_hat - y) ** 2

L.backward()
```




CG in PyTorch: backward

```
x = torch.tensor([2.])
w = torch.tensor([1.],
    requires_grad=True)
y = torch.tensor([3.])

y_hat = x * w
L = (y_hat - y) ** 2

L.backward()
```




CG in PyTorch: backward

```
x = torch.tensor([2.])
w = torch.tensor([1.],
    requires_grad=True)
y = torch.tensor([3.])

y_hat = x * w
L = (y_hat - y) ** 2

L.backward()
```



Computational Graph in PyTorch

```
x = torch.tensor([2.])
w = torch.tensor([1.],
    requires_grad=True)
y = torch.tensor([3.])

y_hat = x * w
L = (y_hat - y) ** 2

L.backward()

print(w.grad)
print(x.grad)

tensor([-4.])
None
```

$x=2$
x.grad=None

$w=1$
w.grad=-4

Computational Graph in PyTorch



```
x = torch.tensor([2.])
w = torch.tensor([1.],
    requires_grad=True)
y = torch.tensor([3.])

y_hat = x * w
L = (y_hat - y) ** 2

L.backward()

L = (x * w - y) ** 2
L.backward()

print(w.grad)
```



Autograd

Disable Gradients

```
print(x.requires_grad)
print((x ** 2).requires_grad)


with torch.no_grad():
    print((x ** 2).requires_grad)
```

True
True
False


Back to NumPy

```
np_out = out.detach().cpu().numpy()
```

Backpropagation



Optimizers



$$\text{SGD: } w \leftarrow w - \alpha \cdot \frac{\partial L}{\partial w}$$

Create an SGD optimizer

```
optimizer = torch.optim.SGD(model.parameters(), lr=learning_rate)
```

Reset Gradients

```
optimizer.zero_grad()
```

Perform an optimization step

```
optimizer.step()
```

Putting it All Together – Fashion MNIST Classification



Putting it All Together

1. Hyperparameters
2. Handling Data
3. Model, Loss, Optimizer
4. Training and Inference
5. Overall Training Process



1. Hyperparameters

```
# configurations
LR = 1e-3 # learning rate
B_SQRT = 8
B = B_SQRT**2 # batch size
EPOCHS = 100 # num epochs
INPUT_SIZE = 28 # input size

device = 'cuda' if torch.cuda.is_available() else 'cpu'
```

2. Handling Data

```
# handling data
training_data = datasets.FashionMNIST(
    root="data",
    train=True,
    download=True,
    transform=ToTensor()
)

val_data = datasets.FashionMNIST(
    root="data",
    train=False,
    download=True,
    transform=ToTensor()
)
```



Downloading datasets

Setting dataset manager

- Automatic batching
- Customized data loading order
- ...

3. Model, Loss, Optimizer

```
# define model
model = nn.Sequential(
    nn.Flatten(),
    nn.Linear(INPUT_SIZE*INPUT_SIZE, 512),
    nn.ReLU(),
    nn.Linear(512, 512),
    nn.ReLU(),
    nn.Linear(512, 10),
)

# move to correct device
model.to(device)
```

```
# define loss
criterion = nn.CrossEntropyLoss()

# define optimizer
optimizer = torch.optim.SGD(model.parameters(), lr=LR)
```

4. Training and Inference

Training Loop


```
# iterate through all batches
for batch, (X, y) in enumerate(dataloader):
    # move data to device
    X, y = X.to(device), y.to(device)
    # forward pass
    pred = model(X)
    loss = criterion(pred, y)
    # new gradients per batch
    optimizer.zero_grad()
    # backward pass
    loss.backward()
    # update
    optimizer.step()
```

Inference Loop

```
# disregard gradients when not training
with torch.no_grad():
    # iterate through all batches
    for X, y in dataloader:
        # move data to device
        X, y = X.to(device), y.to(device)
        # forward pass
        pred = model(X)
```

5. Overall Training Process

```
for t in range(EPOCHS):
    train_res = train_loop(train_dataloader, model, criterion, optimizer)
    val_res = inference_loop(val_dataloader, model, criterion)
```





Weights & Biases

TensorBoard

Parameters search

Monitor experiments

Visualizations



nn.functional

Tensor

hooks

AutoGrad

nn.Module

torchvision

...

PyTorch

e i n o p s

Transforms

A

Albumentations

kornia

**Next Monday:
No class (Christmas)**

**Next Wednesday:
CNNs**